



AWASHI ME 75-6

- Designed to deliver working speed and power from a light weight unit.
- Has excellent stability and smooth operation, fine accurate movement with joystick controls.

In addition to improving access And Stability on job sites these units are With rubber tracks to avoid scuffing And damage on concrete floors.

Easily transportable, lifting is easy as Four lifting points are provided.



SPECIFICATIONS

MODEL		UNIT	ME 75-6
Machine weight	Cabin rubber	kg	7,430
	Cabin steel		
Standard bucket capacity / width		m ³ /mm	0.25 / 750
Engine	Type		MITSUBISHI S4S
	Displacement	cc	3,331
	Rated output	kW(PS)/min ⁻¹	40.8(55.5) / 2300
Dimensions	Overall length	mm	6,255
	Overall width		2,150
	Overall height		2,555
Working range	Max. digging depth	mm	3,980
	Max. vertical digging depth		3,215
	Max. digging height		6,510
	Max. dumping height		4,535
	Max. digging radius		6,660
	Reach at ground		6,490
	Min. slew radius front swing		2,450
			1,925
	Rear slew radius		1,570
Boom swing angle L/R		deg	L80 / R50



مؤسسة الواسط لتجارة المعدات AL WASIT MACHINERY TRAD. EST.

MODEL		UNIT	ME 75-6
Performance	Max. digging force (Bucket)	kN	53.6
	Max. digging force (Arm)		39.8
	Max. drawbar pull		80.1
	Travel speed (low)(high)	km / h	3.1 / 4.8
	Slew speed	min	9.7
	Gradeability	Angle	30°
Hydraulic system	Pump type		Piston 2+Gear 1
	oil flow	lit / min	78.2 / 78.2 / 46.7
	PTO oil flow	lit / min	78.2
Underbody	Main relief pressure	Mpa	25.5 / 25.5 / 25.5
	Dozer blade width x height	mm	2,150 x 510
	Shoe width x tumbler center		450 x 2,196
	Ground pressure	kPa	34
	Cabin rubber Cabin steel		34.4
	Type of travel motor		Piston shoe-in type
Capacity	Crawler tension system		Grease cylinder
	Hyd. Tank capacity	lit.	85
	Fuel tank capacity		130
	Engine oil capacity		7.5
	Cooling water capacity		10
Noise level LwA / LpA		dB	98 / 78