



## AWM FLATBED SEMI-TRAILER , 3 AXLES FOR 40 FT. CONTAINER.

**DIMENSION :**

12,600 x 2,500 mm

**FRAME:**

Steel T frame. 500mm longitudinal beam: Top flange and bottom flange is 16/16 web plate thickness 8mm. Cross members: 10 channel intervals 600mm. Cap shape steel 7 pieces: 3 pieces in the middle of longitudinal beams, 2 pieces in the left side, 2 pieces in the right side. Outside stake bar : 10 channel steel, 12 pieces, net height is 1.3 m.

**AXELS :**

Three (3) axels Fuwa 16 T wheelbase =1360

**TIRES :**

Thirteen (13) set, Twin arranged pneumatic tires mounted on disc wheels. 12.00 - R24 (one spare set is included ).

**RIM :**

Thirteen (13) set , 8.5-24 (one spare set is included)

**SUSPENSION :**

Three sets CIMC reinforced type suspension

**KINGPIN :**

Size 3.5 inch, adjustable JOST KZ1412

**PAYLOAD :**

Around 60,000 kg.

**LOCKS :**

12 Pieces twist locks for one 40 ft. container or two 20 ft. container.

**FLOOR :**

3mm thickness checkered plate.

**LIGHTING EQUIPMENT :**

24 volts. Rear combined lights for brake, back-up, turning and clearance. Side and front clearance lights.

**STANDARD ACCESSORIES :**

Rubber mud flaps rear bumper.

**FINISH :**

White anti-seawater, whole FLATBED SEMITRAILER FOR 40FT CONTAINER will be waxed in order to get protection from sea water.

